

TD.431 – TECHNICAL DATA: TEXTURE-PAVE™ Pre-Mixed Overlay

Revised: 1.10.16

Product Name: TEXTURE-PAVE™ Pre-Mixed Overlay

Product Class: Dry, Redispersible, Polymer Modified, Cement based Mortar

Use Applications:

- For thin surface repairs and resurfacing of concrete substrates.
- For creating thin architectural/decorative overlays, included but not limited to thin stamped overlays, seamless interior flooring, stenciled cement and more.
- For creating repair and patching mixes for concrete surfaces.
- For regrading concrete surfaces.

Key Features:

- Better overall performance than most other resins, modifiers and polymers, including: Acrylic, polyvinyl acetate, VAE, styrene and silicone.
- Provides a permanent bond (with correct substrate preparation on stable concrete surfaces above grade).
- Increased levels of finish options, moisture resistance, flexural and tensile strengths.
- Increased texturing capabilities.
- Exceptionally long pot life.
- Increase versatility and application range.
- Can be colored integrally with PORTION CONTROL COLORANT™ (PCC) or SYNTHETIC PRIMARY PIGMENT™ (SYPP).
- Can be colored/stained topically with ULTRA-STONE™ Antiquing Stain, CHEM-STONE™ Reactive Stain or HYDRA-STONE™ Dye Stain.

Product Properties:

- Appearance – Fine Powder
- Smell – N/A
- Nonvolatile Content % - N/A
- GT Temperature – N/A
- Flammability - N/A
- Weight, Lb. Per stock container – 55 lbs.
- Application temperature - 40° - 100° F
- Cured:
 - 70% - 7 dry days @ 70° F
 - 100% - 28 days
- Resistance to moisture deterioration - Excellent
- Resistance to weather, including UV and freeze/thaw cycles - Excellent

Available Packaging:

- Stock – 55 lbs. bags, 56 bags per pallet, 14 pallets per standard truck load
- Color: White
- Special Order - Inquire

Suggested Storage:

- Keep Dry
- Shelf Life - 6 months to a year