

TD.449 – TECHNICAL DATA: CXS-37R™ Clear Sealer

Revised: 3/16/2023 Version: 1.3

Product Description:

CXS-37R™ is a waterborne, thin film build sealer which is NMP/NEP free, and is designed to give a gloss finish with high abrasion resistance. Based on state of the art, self-crosslinking technology that cures as the wet film dries.

Features:

- NMP and NEP free, complies with European regulatory requirements
- Meets current US, Canadian, and EU VOC regulations
- Excellent wear properties and chemical resistance
- Adhesion to multiple substrates
- Interior floor sealer designed for cementitious overlays and concrete substrates

Physical Properties

@73° F / 23° C, 50% R.H.

Taber abrasion	19mg loss
Appearance	Translucent to slightly cloudy dispersion
Total solids by weight %	37.0 ± 1.0
Total solids by volume %	36.7 ± 1.0
Density	8.69 (1.04) lbs/gal (g/ml)
Brookfield viscosity	<100 cps
pH	8.0-9.0
Volatile organic content	2.5 wt % (<50 g/L)
MFFT	<4.4 °C
Freeze-thaw stability	Protect from freezing

Coverage rate:

- Two coat application required at a coverage of 250 ft² / 1 gallon (23.23 m² / 3.78 liters)

Suggested Storage:

- Store in a temperature and weather-controlled area between 65° F / 18° C and 85° F / 29° C.
- Do not allow to freeze.
- Shelf Life: 1 year in original unopened containers.

Available packaging:

- 1 gal, 5 gal, or 55 gal drums (special order only)